

Central Texas Metal Roofing Supply Co., Inc.

Description

The BattLoc Series of panels are specifically designed for use in roofing, mansard and fascia applications. The simple pan design, combined with the snap on batten make these panels ideal for applications where transitions from roof to fascia are required. The 5/8" and the 1" BattLoc profiles can be curved down to a 10' convex curve, perfect for barrel vault applications.

Features


- 5/8", 1", 1 1/2", and 2" Seam Heights
- Variable Panel Widths from 9 3/4" up to 20 1/4".
- Lengths up to 45'.
- Striated pan standard; Optional smooth without striations.
- Optional factory applied sealant in female batten cap.
- Convex Curved BL-058 and BL-100 to a 10'-0" Radius.
- Tapered Panels available up to 29'.
- Minimum 3:12 pitch recommended.
- Waterproof, solid substrate required.

Performance / Testing

- UL 580 Class 90 Wind Uplift Rated.
- UL 2218 Class 4 Impact Rated.
- UL 790 Class A Fire Rated.



Smooth Panel



Striated Panel



Substrates

- 26, 24, 22 Ga Acrylic Coated Galvalume.
- 26 Ga SMP Color Finish.
- 24 Ga Kynar500 Color Finish.
- 26 & 24 Ga Paint Grip.
- 16 & 20 oz. Copper.
- .032 & .040 Aluminum, Anodized or Kynar500 Color Finish.

Austin

830 Sagebrush Drive Austin, Texas 78758
 (512) 452-1515 (800) 428-7412
 Fax (512) 833-7499

www.ctmrs.com

email: info@ctmrs.com

Seguin

720 West IH 10 Seguin, Texas 78155
 (830) 379-3600 (877) 622-8677
 Fax (830) 379-8753